



FICHA TECNICA

CALIDAD TAPIZ:

CINTA

USO/NIVEL:

COMPETICIÓN – USO INTENSO

CARACTERISTICAS TECNICAS:

5/64" velours	5/64" velours	5/64" Velours	5/64" cut pile
100% PA IMPREL®	100% PA IMPREL®	100% PA IMPREL®	100% PA IMPREL®
RUG Action back	DOSSIER Action back	RÜCKEN Action back	BACKING Action back
POOLHOOGTE ± 6,5 mm	HAUTEUR DU VELOURS ± 6,5 mm	POLHÖHE ± 6,5 mm	PILE HEIGHT ± 6,5 mm
TOTALE HOOGTE ± 9 mm	HAUTEUR TOTALE ± 9 mm	GESAMTHÖHE ± 9 mm	TOTAL HEIGHT ± 9 mm
POOLGEWICHT ± 750 g/m ²	POIDS DU VELOURS ± 750 g/m ²	POLGEWICHT ± 750 g/m ²	PILE WEIGHT ± 750 g/m ²
TOTAAL GEWICHT ± 1.700 g/m ²	POIDS TOTAL ± 1.700 g/m ²	GESAMTGEWICHT ± 1.700 g/m ²	TOTAL WEIGHT ± 1.700 g/m ²
AANTAL NOPPEN/M ² ± 405 000	NOMBRE DE POINTS/M ² ± 405 000	NOPPEN/M ² ± 405 000	TUFT DENSITY/M ² ± 405 000
LICHTECHTHEID ≥ 5	RÉSISTANCE À LA LUMIÈRE ≥ 5	LICHTECHTHEIT ≥ 5	LIGHT FASTNESS ≥ 5
WATERECHTHEID ≥ 4-5	RÉSISTANCE À L'EAU ≥ 4-5	WASSERECHTHEIT ≥ 4-5	WATER RESISTANCE ≥ 4-5
WARMTEDOORLAATWEERST. ± 0,13 m ² K/W	RÉSISTANCE THERMIQUE ± 0,13 m ² K/W	WÄRMEDURCHLASSWIDERST. ± 0,13 m ² K/W	THERMAL RESISTANCE ± 0,13 m ² K/W
BRANDKLASSE Cfl-s1 (EN 13501-1) indien verkleefd	CLASSEMENT FEU Cfl-s1 (EN 13501-1) en pose collée	BRANDKLASSE Cfl-s1 (EN 13501-1) verklebt	FIRE CLASS Cfl-s1 (EN 13501-1) if glued

HOMOLOGACIONES / CERTIFICACIONES / PICTOGRAMAS:



***** Datos protegidos por el Secreto Empresarial